

- Help support for interpretation of results and creation of sequences

**( E** 





# **INTELLIGENCE**

The VT1® device intended for use in Occupational Health and Preventive Medicine departments.

3-patent innovative technology.

A combination of optical, electronic and computing high technology to perform visual acuity measurements and screen for visual problems.

- Adapted for wearers of progressive lenses. Move from far to near vision simply by lowering the
- A sensitive detector and ergonomic forehead rest

ensure optimum facial position

Complete visual field analysis A patented motorized system tests 32 points per eye from 20°-30° for central visual field.



# WHEN SIMPLICITY GOES HAND IN HAND

The VT1® software is intuitive, quickly and efficiently performing your tests within minutes:



The pack is the best option to benefit from the VT1 software and LCD remote control at the best price.


Drive your device from your computer or remote control at your convenience.

# A PANEL OF TESTS


# FROM BASIC TO DETAILED

So as not to overlook a serious illness the **VT1®** world offers a large choice of tests.

We are developing alongside your profession.



- 1-2. Acuity and Hyperopia 20/20-20/100.3. Amsler.4. Astigmatism.5. Depth perception.6. Colours.7. Phorias.
- 8. Contrast. 9. Complete visual field. 10. Fusion test. 11. Visual field.



Visual field test

# **DEPISTEO** innovation

Standard visual field in a compact screening device

# COMPLETE VISUAL FIELD **TEST**

With a total of 84 light stimuli, the **VT1**® tests central field (20° - 30°), horizontal field (180°), vertical field ( $\pm 22^{\circ} \pm 30^{\circ}$ ) and nasal field (50°). Most central disorders are due to retinal problems such as ARMD.



**Glare sensitivity,** when there is too much light for the eye to cope with.

**Glare resistance** is the recovery time required after being blinded. These two additional tests are intended for professional vehicle drivers.

# Did you know?

At 80 miles/hour our vision is reduced to 30°. This concerns everyone, not only professional vehicle drivers. An increase in recovery time could be caused by: astigmatism, advancing age, cataracts and poor compensation.

# VT1V0200ENG04-2019. This medical device is a regulated health product and thus bears the CE marking. DEPISTEO reserves the right to modify the features and performance of the VT1\* without prior notice. Please read the User Manual before use.

# COMPARE THE MODELS AND CHOOSE YOUR OWN

	VT1 MASTER GT EDITION	VT1 MASTER EDITION
BASIC TESTS	GI EDITION	EDITION
LETTERS (BINO & MONO)	•	
LANDOLT RINGS (BINO & MONO)	•	•
AMSLER	•	
HYPEROPIA TEST	•	-
DEPTH PERCEPTION	•	
FUSION	•	•
ASTIGMATISM	•	
VERTICAL & HORIZONTAL PHORIAS	•	
ISHIHARA TYPE COLOURS TEST	•	
HORIZONTAL AND VERTICAL VISUAL FIELD	•	•
ADDITIONAL TESTS		
CENTRAL VISUAL FIELD	•	
GLARE SENSITIVITY	•	
GLARE RESISTANCE	•	
CONTRAST SENSITIVITY	•	•
CHILDREN ACUITY	•	
CHILDREN PHORIAS	•	
FUNCTIONS		
FAR VISION	•	•
INTERMEDIATE VISION	•	•
NEAR VISION	•	•
HIGH PHOTOPIC	•	•
LOW PHOTOPIC	•	•
MESOPIC (NIGHT VISION)		•
DRIVING MODE  Glare Sensitivity, Glare Resistance et Central Visual Field tests are not available	PREMIUM VERSION	STANDARD VERSION
on the LCD remote control	± ± .	+



Australian Distributor

SONIC

1800 639 263 info@soniceq.com soniceq.com

WARRANTY DIMENSIONS 57 x 43 x 35 cm / 21 x 14 x 18' WEIGHT LIGHTING CONDITIONS 4.8 kg / 10.7 lbs High photopic (160 candelas)
Low photopic (80 candelas) (NOMINAL VALUES) Mesopic night vision (3 candelas)
Lit by 16 white LEDs driven LIGHTING SYSTEM by microcontroller and diffuser system DISTANCES Far vision 5m ± 0.1 m / 16.4' ± 0.4'
 Intermediate vision 60 cm ± 0.5 cm / 23.6' ± 0.2' Near vision 33 cm ± 0.25 cm / 13.0' ± 0.1'
 Hyperopia lenses: +1 diopter TEST BAND High definition photographic film Time between two neighbouring tests: 700ms Time to go from one slide to another: 1s REACTIVITY TEST TIME · Routine test: 3 minutes In-depth test: 5 minutes OPERATING TEMPERATURE HUMIDITY between 15 and 35°C / between 59 and 95°F 75% maximum POWER SUPPLY 12 VDC from an external medical power supply POWER REFERENCE STANDARDS 24W EN60601-1, EN60601-1-2, NF EN ISO 8596 MARKING MEDICAL CLASS CE Class I

THE VT1 IS AVAILABLE IN "PACK" VERSION (SOFTWARE & REMOTE CONTROL) OR SIMPLY IN COMPUTERIZED VERSION (SOFTWARE). WHATEVER CATCHES OUR EYE!

APPLIED PART

Type B



550 Pharr Road, NE, Suite 201 Atlanta GA 30305 Phone: +1 800 496 8290 Fax: + 1 800 496 8290 contact@depisteo.com  $C \in$